

# HUNT HEATING

Hydronic Systems (Australia) Pty. Ltd.

11 Fiveways Blvd, Keysborough, Vic 3173 T: 1300 00 1800 F: (+61 3) 9798 5133

Postal Address: P.O. Box 294, Braeside, Victoria 3195

[www.huntheat.com.au](http://www.huntheat.com.au)

## FERNOX

### PROTECTOR ALPHI-11

- Protects against corrosion and limescale
- Maintains efficiency so extending system life
- Prevents bacterial contamination
- Compatible with all metals and materials commonly used in heating systems
- Non-toxic, environmentally friendly
- Combined antifreeze and protector
- Protects heating, chilled water and solar systems



#### Product Uses

Fernox Protector Alphi-11 is a combined antifreeze and inhibitor, which gives long term protection of domestic central heating systems against internal corrosion and limescale formation. It prevents corrosion of all metals found in these systems, i.e. ferrous metals, copper and copper alloys and aluminium. It is especially recommended for use in solar systems. Fernox Protector Alphi-11 is compatible with all metals and materials commonly used in central heating systems.

For continued protection we recommend Protector levels are checked regularly (annually). The concentration of the product can be easily measured on site using a Fernox Protector test kit.

#### Physical Properties

Fernox Protector Alphi-11 contains mono-propylene glycol.

Colour: Colourless  
Odour: Mild  
Form: Clear liquid  
pH (conc) 5.7 – 6.1  
pH (soln 25%): 7.0 – 7.5  
SG: 1.04 at 20°C

#### Application and Dosage

The minimum recommended "in-use" concentration of the product is 25% in order to ensure adequate corrosion protection. This concentration will protect down to -11°C. A concentration of 40% will protect down to -22°C. Protector Alphi-11 can be introduced via the feed and expansion tank or other suitable point of application, e.g. radiator, using a Fernox Injector. Introduce into the system after having drained a quantity of water at least equal to the amount of Alphi-11 to be added. Engage the circulating pump and have the system online for a few hours in order to achieve an even distribution.

Concentration	25%	30%	35%	40%
Protection	-11°C	-15°C	-18°C	-22°C

In single feed indirect cylinders, e.g. "Primatic" or similar, potable water chemicals must be used.

We recommend untreated systems are thoroughly cleansed and flushed, in accordance with BS7593 and Benchmark, using Fernox Restorer before treating with Fernox Protector Alphi-11 as existing debris can damage the installation.

#### Packaging, Handling and Storage

Fernox Protector Alphi-11 is supplied in 5 and 25 litre containers.

Fernox Protector Alphi-11 is classified as non-hazardous and non-irritant, but as with all chemicals keep out of reach of children. Do not mix with other chemicals with the exception of Fernox products. Do not take internally. In case of contact with eyes or skin, rinse immediately with plenty of water.